



Changes of Claims Shown by Markings

--- An amendment paper

7/12/2006

This amendment paper is to replace the prior one dated 3/31/2006. All bracketing and underlining is made in comparison to the original patent, not in comparison to any prior amendment in the reissue application.

[Note] There are two portions in the new claims, i.e., claims 1-9 and claims 10-15. Claim 1 and claim 10 are the two independent claims. Claims 1-9 are used to cover the situation with respect to a beam expanding laser cavity. Claims 10-15 are used to cover the situation with respect to a regular laser cavity. Each of them is very similar to the set of claims 1-9 in Pat. 6,373,868, in which only one independent claim covers these two situations. In other words, now claims 1-9 have been kept almost the same as before, except that the contents related to a regular laser cavity have been taken away. And then new claims 10-15 are added for the situation of the regular laser cavity.

What is claimed is:

1. (amended) In a method for configuring a standing-wave cavity arrangement for solid-state lasers in obtaining stable single-mode operation, whereby overcoming the major difficulty, with intracavity frequency conversions, typically in frequency doubling caused by the so-called "green problem", comprising the steps of
 - (1) constructing a forming means for said cavity, including at least two end mirrors, wherein said cavity is a beam expanding laser cavity;
 - (2) constructing a pump head means placed within said cavity for lasing at a fundamental wavelength; comprising the steps of
 - A. selecting a solid-state laser medium means;
 - B. selecting a pump source means including laser diode bars to provide relevant pumping beams for pumping said laser medium means; and
 - C. producing a gain region within said laser medium means by said pump source means [~~pumping beams~~];
 - (3) constructing a formation of wavelength selectivity with low insertion losses placed within said cavity, wherein the performance parameters of said formation are predetermined whereby to sufficiently and uniquely determine the laser's oscillating frequency and to force the laser to perform a stable single-mode or narrow band operation; and

- (4) selecting an approach for promoting single longitudinal mode operation ~~[eliminating or minimizing the spatial hole burning effect]~~ from the group consisting of
 - A. a first approach, comprising
 - 1) creating said gain region within a narrow area along the optical axis of said cavity and immediately adjacent to one of said end mirrors, and
 - 2) selecting said formation from the group consisting of
 - ~~{a) a first formation comprising a monochromatic polarizer means;}~~
 - b[1]) a first [second] formation, built up of a Lyot filter and a one-dimensional beam expander means, and
 - b[2]) a second [third] formation, built up of a spectral filter means including at least one spectral filter, and a two-dimensional beam expander means to reduce insertion losses for said spectral filter means substantially; and
 - ~~{d) a fourth formation comprising an etalon; and}~~
 - B. a second approach, comprising
 - 1) placing said pump head means between a pair of quarter-wave plates whereby producing the “twisted mode” operation, and
 - 2) building said formation up of a spectral filter means consisting of at least one spectral filter, and a beam expander means to reduce insertion losses for said spectral filter means substantially.
2. In the method of claim 1, wherein said approach is said first approach, further comprising the steps of
 - (1) using a nonlinear crystal means arranged in an optimal condition including phase-matching for intracavity frequency conversion;
 - (2) maintaining the bandwidth of said formations to be smaller than the laser longitudinal oscillating mode interval of said cavity, and its free spectral range is larger than the FWHM of lasing bandwidth of the gain medium;
 - ~~{(3) building said monochromatic polarizer means up of a polarizer and said nonlinear crystal means;}~~
 - (3[4]) selecting said spectral filter from the group [consisting of] including
 - A. Lyot filters, formed by a polarizing means and a birefringent element; and
 - B. etalons, including 1) regular etalons, and 2) birefringent etalons which acts likewise as an additional Lyot filter in conjunction with said polarizing means;
 - (4[5]) selecting said polarizing means from the group consisting of 1) Brewster plate, 2) Brewster surface, and 3) Brewster reflector;
 - (5[6]) selecting said birefringent element from the group consisting of 1) said nonlinear crystal means, and 2) said birefringent etalon;

(6[7])selecting said laser cavity from the group [consisting of] including 1) regular standing-wave cavities; 2) V-shaped standing-wave cavities; and 3) L-shaped standing-wave cavities;

(7[8])building said two-dimensional beam expander means up of an AR coated lens pair; which additionally comprises the steps of

- A. placing an aperture means at the focal plane of said object lens where a diffraction-limited point occurs, so that said beam expander means is configured as a spatial filter likewise in conjunction with said aperture means, whereby leading to TEM.sub.00 mode operation and an output with an excellent spatial quality;
- B. keeping a proper defocusing for said beam expander means whereby achieving compensation of the thermal lens effect leading to stable laser operations; and
- C. locating said nonlinear crystal means adjacent to said aperture means or within the unexpanded beam portion.

9. (amended) In the method of claim 1, further selecting a nonlinear crystal means arranged in an optimal condition including phase-matching for intracavity frequency conversion, wherein said frequency conversion includes

(1) second harmonic generation, wherein said nonlinear crystal including KTP;

(2) resonantly enhanced second harmonic generation, wherein

- A. said nonlinear crystal means including KTP;
- B. said formation [spectral filter] is a [said] regular etalon; and
- C. said cavity arrangement is configured to resonate at said second harmonic frequency by a phase compensator means or cavity distance adjustor means whereby largely enhancing the intensity of said second harmonic radiation and the conversion efficiency;

(3) third harmonic generation, wherein

said nonlinear crystal means is two nonlinear crystals positioned serially, in which the first crystal is set with type I phase-matching for doubling said fundamental radiation to produce the SHG, and the second crystal is set with type II phase-matching to mix said fundamental and second harmonic radiations so as to produce the THG;

(4) third harmonic generation with resonant harmonic generation, wherein

- A. said nonlinear crystal means is two nonlinear crystals positioned serially, in which the first crystal is set with type I phase-matching for doubling said fundamental radiation to produce the SHG, and the second crystal is set with type II phase-matching to mix said fundamental and second harmonic radiations so as to produce the THG;
- B. said formation [spectral filter] is a [said] regular etalon; and

- C. said cavity arrangement is configured to resonate at said second harmonic frequency by a phase compensator means or cavity distance adjustor means whereby largely enhancing the intensity of said second harmonic radiation and the conversion efficiency;
- (5) fourth harmonic generations, wherein
 - said nonlinear crystal means is three nonlinear crystals positioned serially, in which the first crystal is set with type I phase-matching for doubling said fundamental radiation to produce the SHG, the second crystal is set with type II phase-matching to mix said fundamental and second harmonic radiations for producing the THG, and the third crystal is set with type I phase-matching to mix said fundamental and third harmonic radiations so as to produce the FHG;
- (6) fourth harmonic generation with resonant harmonic generation, wherein
 - A. said nonlinear crystal means is two nonlinear crystals positioned serially, in which the first crystal is used for doubling said fundamental radiation to a second harmonic radiation, and the second crystal is for doubling said second harmonic radiation to a quadrupling harmonic radiation;
 - B. said formation [spectral filter] is a [said] regular etalon; and
 - C. said cavity arrangement is configured to resonate at said second harmonic frequency by a phase compensator means or cavity distance adjustor means whereby largely enhancing the intensity of said second harmonic radiation and the conversion efficiency;
- (7) frequency mixing, wherein
 - A. further selecting an input radiation, including a resonantly enhanced input; and
 - B. said nonlinear crystal means mixes said fundamental and said input radiations to a mixing radiation; and
- (8) frequency mixing with resonant harmonic generation, wherein
 - A. further selecting an input radiation;
 - B. said nonlinear crystal means is two nonlinear crystals positioned serially, in which the first crystal is used for doubling said fundamental radiation to produce the SHG, and the second crystal mixes said second harmonic and said input radiations to a mixing radiation;
 - C. said formation [spectral filter] is a [said] regular etalon; and
 - D. said cavity arrangement is configured to resonate at said second harmonic frequency by a phase compensator means or cavity distance adjustor means whereby largely enhancing the intensity of said second harmonic radiation and the conversion efficiency.

10. In a method for configuring a standing-wave cavity arrangement for solid-state lasers in obtaining stable single-mode operation, whereby overcoming the major difficulty with intracavity frequency

conversions, typically in frequency doubling caused by the so-called “green problem”, comprising the steps of

- (1) constructing a forming means for said cavity, including at least two end mirrors, wherein said laser cavity is a regular laser cavity without a beam expander;
- (2) constructing a pump head means placed within said cavity for lasing at a fundamental wavelength; comprising the steps of
 - A. selecting a solid-state laser medium means;
 - B. selecting a pump source means including laser diode bars to provide relevant pumping beams for pumping said laser medium means; and
 - C. producing a gain region within said laser medium means by said pump source means;
- (3) constructing a formation of wavelength selectivity with low insertion losses placed within said cavity, wherein the performance parameters of said formation are predetermined whereby to sufficiently and uniquely determine the laser’s oscillating frequency and to force the laser to perform a stable single-mode or narrow band operation; and
- (4) creating said gain region within a narrow area along the optical axis of said cavity and immediately adjacent to one of said end mirrors.

11. In the method of claim 10, said formation including

- (1) a first formation comprising a monochromatic polarizer means; and
- (2) a second formation comprising an etalon.

12. In the method of claim 11, further comprising the steps of

- (1) using a nonlinear crystal means arranged in an optimal condition including phase-matching for intracavity frequency conversion;
- (2) maintaining the bandwidth of said formation to be smaller than the laser longitudinal oscillating mode interval of said cavity, and its free spectral range is larger than the FWHM of lasing bandwidth of the gain medium;
- (3) building said monochromatic polarizer means up of a polarizer and said nonlinear crystal means; and
- (4) selecting said laser cavity from the group including 1) regular standing-wave cavities; 2) V-shaped standing-wave cavities; and 3) L-shaped standing-wave cavities.

13. In the method of claim 12, in order to protect the laser polarization at the fundamental wavelength from being altered or affected by the amount of birefringence of said nonlinear crystal means and said laser medium means; further comprising the steps of

- (1) keeping said nonlinear crystal means to have a constant effective length to produce a phase retardation to be a half integral multiple of said fundamental wavelength; and
- (2) selecting said laser medium from the group including 1) nonbirefringent laser medium, 2) laser medium made and oriented without the exhibition of birefringences, and 3) birefringent laser medium having a constant effective length to produce a phase retardation to be a half integral multiple of said fundamental wavelength.

14. In the method of claim 12, further comprising the steps of

- (1) maintaining a constant cavity length whereby stabilizing operation frequency;
- (2) maintaining a constant temperature for said nonlinear crystal means whereby providing the best result for frequency conversion and minimizing cavity losses for the oscillating mode; and
- (3) constructing a wavelength tuning form for the alignment of said etalon transmission peak to said laser oscillation frequency.

15. In the method of claim 10, further selecting a nonlinear crystal means arranged in an optimal condition including phase-matching for intracavity frequency conversion, wherein said frequency conversion includes

- (1) second harmonic generation, wherein said nonlinear crystal including KTP;
- (2) resonantly enhanced second harmonic generation, wherein
 - A. said nonlinear crystal means including KTP;
 - B. said formation is a regular etalon; and
 - C. said cavity arrangement is configured to resonate at said second harmonic frequency by a phase compensator means or cavity distance adjustor means whereby largely enhancing the intensity of said second harmonic radiation and the conversion efficiency;
- (3) third harmonic generation, wherein
 - said nonlinear crystal means is two nonlinear crystals positioned serially, in which the first crystal is set with type I phase-matching for doubling said fundamental radiation to produce the SHG, and the second crystal is set with type II phase-matching to mix said fundamental and second harmonic radiations so as to produce the THG;
- (4) third harmonic generation with resonant harmonic generation, wherein
 - A. said nonlinear crystal means is two nonlinear crystals positioned serially, in which the first crystal is set with type I phase-matching for doubling said fundamental radiation to produce the SHG, and the second crystal is set with type II phase-matching to mix said fundamental and second harmonic radiations so as to produce the THG;
 - B. said formation is a regular etalon; and

- C. said cavity arrangement is configured to resonate at said second harmonic frequency by a phase compensator means or cavity distance adjustor means whereby largely enhancing the intensity of said second harmonic radiation and the conversion efficiency;
- (5) fourth harmonic generations, wherein
- said nonlinear crystal means is three nonlinear crystals positioned serially, in which the first crystal is set with type I phase-matching for doubling said fundamental radiation to produce the SHG, the second crystal is set with type II phase-matching to mix said fundamental and second harmonic radiations for producing the THG, and the third crystal is set with type I phase-matching to mix said fundamental and third harmonic radiations so as to produce the FHG;
- (6) fourth harmonic generation with resonant harmonic generation, wherein
- A. said nonlinear crystal means is two nonlinear crystals positioned serially, in which the first crystal is used for doubling said fundamental radiation to a second harmonic radiation, and the second crystal is for doubling said second harmonic radiation to a quadrupling harmonic radiation;
- B. said formation is a regular etalon; and
- C. said cavity arrangement is configured to resonate at said second harmonic frequency by a phase compensator means or cavity distance adjustor means whereby largely enhancing the intensity of said second harmonic radiation and the conversion efficiency;
- (7) frequency mixing, wherein
- A. further selecting an input radiation, including a resonantly enhanced input; and
- B. said nonlinear crystal means mixes said fundamental and said input radiations to a mixing radiation; and
- (8) frequency mixing with resonant harmonic generation, wherein
- A. further selecting an input radiation;
- B. said nonlinear crystal means is two nonlinear crystals positioned serially, in which the first crystal is used for doubling said fundamental radiation to produce the SHG, and the second crystal mixes said second harmonic and said input radiations to a mixing radiation;
- C. said formation is a regular etalon; and
- D. said cavity arrangement is configured to resonate at said second harmonic frequency by a phase compensator means or cavity distance adjustor means whereby largely enhancing the intensity of said second harmonic radiation and the conversion efficiency.